

Page 1/13

Printing date: 24.09.2021 Revision date: 24.09.2021 Version no. 16 Bezbednosni list Na osnovu Sl. gl. RS br. 100/11

SECTION 1: Identifikacija hemikalije i podaci o licu koje stavlja hemikaliju u promet

- 1.1 Product identifier
- Trade name: BODY PROLINE 635 5:1 PRIMER
- · Article number: 457
- · **UFI:** 0P01-00XV-X008-XCSG
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9b Fillers, putties, plasters, modelling clay
- · Process category PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
- · Environmental release category ERC2 Formulation into mixture
- · Article category AC1 Vehicles
- · Application of the substance / the mixture Surface protection
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

Further information obtainable from:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com


SECTION 2: Identifikacija opasnosti

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Lig. 3 H226 Flammable liquid and vapour.



Repr. 2 H361d Suspected of damaging the unborn child.

Printing date: 24.09.2021 Revision date: 24.09.2021

Version no. 16

Trade name: **BODY PROLINE 635 5:1 PRIMER**



Skin Irrit. 2 H315 Causes skin irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS07

Signal word Warning

Hazard-determining components of labelling:

toluene

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H361d Suspected of damaging the unborn child.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

Use explosion-proof [electrical/ventilating/lighting] equipment. P241

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

Store locked up. P405

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

· 2.3 Other hazards

Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Sastav/Podaci o sastojcima

· 3.2 Chemical characterisation: Mixtures

Description: Mixture of hazardous substances listed below with nonhazardous additions.

Dangerous components:

CAS: 1330-20-7

EINECS: 215-535-7

Index number: 601-022-00-9

RTECS: ZE 2100000

Rea.nr.: 01-2119488216-32-001 01-2119488216-32-002 01-2119488216-32-003

♠ Flam. Liq. 3, H226

Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315

20-<25%

Page 3/13 Bezbednosni list Printing date: 24.09.2021 Na osnovu Sl. gl. RS br. 100/11

Revision date: 24.09.2021

Version no. 16

Trade name: **BODY PROLINE 635 5:1 PRIMER**

CAS: 108-88-3 toluene ≥3-<5%

Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304

EINECS: 203-625-9

Index number: 601-021-00-3

RTECS: XS 5250000

Reg.nr.: 01-2119471310-51-0000

01-2119471310-51-0003 01-2119471310-51-0005 01-2119471310-51-0002 01-2119471310-51-0027

CAS: 13463-67-7 EINECS: 236-675-5

Index number: 022-006-00-2

CAS: 64742-95-6

EINECS: 265-199-0 Index number: 649-356-00-4

Reg.nr.: 01-2119455851-35-0001 📤 Aquatic Chronic 2, H411

& Carc. 2, H351

Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226

Asp. Tox. 1, H304

Flam. Liq. 2, H225

Skin Irrit. 2, H315

titanium dioxide

(1) Acute Tox. 4, H332; STOT SE 3, H335-H336

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: Mere prve pomoæi

- · 4.1 Description of first aid measures
- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Mere za gašenje požara

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

- 5.6 Fire and explosion Hazards
- Speial protective equipment and fire fighting procedures: No special measures required.
- · Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Mere u sluèaju udesa

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

1-<5%

≥2.5-<5%

Page 4/13 Printing date: 24.09.2021 Revision date: 24.09.2021

Version no. 16

Trade name: **BODY PROLINE 635 5:1 PRIMER**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Rukovanje i skladištenje

• 7.1 Precautions for safe handling Open and handle receptacle with care.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Kontrola izloženosti

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene

IOELV (EU) Short-term value: 442 mg/m³, 100 ppm

Long-term value: 221 mg/m³, 50 ppm

Skin

108-88-3 toluene

IOELV (EU) Short-term value: 384 mg/m³, 100 ppm

Long-term value: 192 mg/m³, 50 ppm

Skin

- · Regulatory information IOELV (EU): (EU) 2019/1831
- · **Additional information:** The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection: Not required.

Page 5/13 Printing date: 24.09.2021 Revision date: 24.09.2021

Version no. 16

Trade name: BODY PROLINE 635 5:1 PRIMER

Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- · For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Rubber gloves
- · Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Fizièka i hemijska svojstva

- · 9.1 Information on basic physical and chemical properties
- General Information
- Appearance:

Form: Liquid Colour: Grey

Odour: Characteristic
Odour threshold: Not determined.

pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 137-143 °C (1330-20-7 xylene)

Flash point: 23 - 60 °C

· Flammability (solid, gas): Not applicable.

· Autoignition temperature: 500 °C

• **Decomposition temperature:** Not determined.

• Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Risk of explosion by shock, friction, fire or other sources of ignition.

Explosion limits:

Lower: 1.1 Vol % **Upper:** 7 Vol %

Page 6/13 Printing date: 24.09.2021 Revision date: 24.09.2021

Version no. 16

Trade name: **BODY PROLINE 635 5:1 PRIMER**

Vapour pressure at 20 °C:
 Density at 20 °C:
 Relative density
 Vapour density
 Evaporation rate
 6.7 hPa
 1.512 g/cm³
 Not determined.
 Not determined.
 Not determined.

Solubility in / Miscibility with

water: Fully miscible.

Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

Solvent content:

 Organic solvents:
 28.6 %

 VOC (EC)
 432.1 g/l

 Solids content (volume):
 70.4 %

• 9.2 Other information No further relevant information available.

SECTION 10: Reaktivnost i stabilnost

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toksikološki podaci

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Dermal LD50 9,312 mg/kg Inhalative LC50/4 h >44.5 mg/l

471-34-1 calcium carbonate

Oral LD50 6,450 mg/kg (rat)

1330-20-7 xvlene

 Oral
 LD50
 4,300 mg/kg (rat)

 Dermal
 LD50
 2,000 mg/kg (rabbit)

 Inhalative LC50/4 h
 11 mg/l (ATE)

108-88-3 toluene

Oral LD50 5,000 mg/kg (rat)

Dermal LD50 (static) 12,124 mg/kg (rabbit)

Page 7/13

Bezbednosni list
Printing date: 24.09.2021

Na osnovu Sl. gl. RS br. 100/11

Printing date: 24.09.2021 Revision date: 24.09.2021

Version no. 16

Trade name: **BODY PROLINE 635 5:1 PRIMER**

Inhalative LC50/4 h 5,320 mg/l (mouse)

13463-67-7 titanium dioxide

 Oral
 LD50
 >20,000 mg/kg (rat)

 Dermal
 LD50
 >10,000 mg/kg (rabbit)

Inhalative LC50/4 h >6.82 mg/l (rat)

64742-95-6 Solvent naphtha (petroleum), light arom.

 Oral
 LD50
 >6,800 mg/kg (rat)

 Dermal
 LD50
 >3,400 mg/kg (rab)

 Inhalative LC50/4 h
 >10.2 mg/l (rat)

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging the unborn child.

- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ekotoksikološki podaci

· 12.1 Toxicity

Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

· 12.2 Persistence and degradability

This prouduct contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· 12.5 Results of PBT and vPvB assessment

- · PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic(PBT).
- · **VPvB:** This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

Continue on page 8

Printing date: 24.09.2021 Revision date: 24.09.2021

Version no. 16

Trade name: **BODY PROLINE 635 5:1 PRIMER**

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Odlaganje

- · 13.1 Waste treatment methods
- * **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- European waste catalogue
- HP3 Flammable
- HP4 Irritant skin irritation and eye damage
- HP7 Carcinogenic
- HP10 Toxic for reproduction
- HP14 Ecotoxic
- Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Podaci o transportu

- · 14.1 UN-Number
- ADR, IMDG, IATA UN1263
- · 14.2 UN proper shipping name
- ·ADR **UN1263 PAINT**
- IMDG, IATA **PAINT**
- · 14.3 Transport hazard class(es)
- ADR



Class 3 (F1) Flammable liquids.

Label 3

IMDG, IATA



·Class 3 Flammable liquids.

Label 3

· 14.4 Packing group

ADR, IMDG, IATA Ш

· 14.5 Environmental hazards:

Marine pollutant: No

· 14.6 Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code):

EMS Number: F-E,S-E Bezbednosni list

Page 9/13

Printing date: 24.09.2021

Ra osnovu Sl. gl. RS br. 100/11

Printing date: 24.09.2021 Revision date: 24.09.2021

Version no. 16

Trade name: **BODY PROLINE 635 5:1 PRIMER**

Stowage Category

Α

14.7 Transport in bulk according to Annex II of Marpol

and the IBC Code Not applicable.

Transport/Additional information:

· ADR

Limited quantities (LQ) 5L

• Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

Transport categoryTunnel restriction code

·IMDG

Limited quantities (LQ)Excepted quantities (EQ)Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 1263 PAINT, 3, III

SECTION 15: Regulatorni podaci

•3Y

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS02

GHS07

CLICOC

Signal word Warning

Hazard-determining components of labelling:

toluene

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H361d Suspected of damaging the unborn child.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

Page 10/13

Bezbednosni list
Printing date: 24.09.2021

Na osnovu Sl. gl. RS br. 100/11

Revision date: 24.09.2021 Version no. 16

Trade name: BODY PROLINE 635 5:1 PRIMER

- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

108-88-3 toluene: 3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

108-88-3 toluene: 3

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Ostali podaci

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS: Department of Quality Control

Contact:

HB BODY S.A

Ms Olympia Stamkou

Ph: +30 2310 790 032

fax: +30 2310 790 033

email: stamkou@hbbody.com

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

Page 11/13

Bezbednosni list
Printing date: 24.09.2021

Na osnovu Sl. gl. RS br. 100/11

Revision date: 24.09.2021 Version no. 16

Trade name: BODY PROLINE 635 5:1 PRIMER

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.

RS

Continue on page 12

Page 12/13

Printing date: 24.09.2021

Ra osnovu Sl. gl. RS br. 100/11

Revision date: 24.09.2021 Version no. 16

Trade name: **BODY PROLINE 635 5:1 PRIMER**

Annex: Exposure scenario

· Short title of the exposure scenario

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9b Fillers, putties, plasters, modelling clay
- **Process category** PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
- · Article category AC1 Vehicles
- Environmental release category ERC2 Formulation into mixture
- Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

· Conditions of use According to directions for use.

Duration and frequency

5 workdays/week.

Frequency of use:

Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Used amount per time or activity Smaller than 100 g per application.
- · Other operational conditions
- Other operational conditions affecting environmental exposure Use only on hard ground.
- Other operational conditions affecting worker exposure

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Avoid contact with eyes.

- Other operational conditions affecting consumer exposure No special measures required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- Worker protection

Organisational protective measures

No special measures required.

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

Provide explosion-proof electrical equipment.

Use product only in enclosed systems.

Ensure that suitable extractors are available on processing machines

Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Pregnant women should strictly avoid inhalation or skin contact.

Not required.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Avoid contact with the eyes.

Page 13/13

Bezbednosni list
Printing date: 24.09.2021

Na osnovu Sl. gl. RS br. 100/11

Revision date: 24.09.2021

Version no. 16

Trade name: **BODY PROLINE 635 5:1 PRIMER**

Tightly sealed goggles

Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

Environmental protection measures

Water

Do not allow to reach sewage system.

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Soil

Prevent contamination of soil.

The product is only processed over the concrete collecting basin.

· Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

- **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- Consumer

Not relevant for this Exposure Scenario.

This product is to be used by professional technitians only.

· Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.