

* **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

· **1.1 Product identifier**

· **Trade name:** **SPRAY BODY 692 EXCLUSIVE PRIMER**

· **Article number:** 914

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Life cycle stages** IS Use at industrial Sites

· **Sector of Use** SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Product category** PC9a Coatings and paints, thinners, paint removers

· **Process category** PROC7 Industrial spraying

· **Environmental release category** ERC5 Use at industrial site leading to inclusion into/onto article

· **Article category** AC7 Metal articles

· **Technical function** Other

· **Application of the substance / the mixture** Surface protection

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

· **Further information obtainable from:**

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

· **1.4 Emergency telephone number:**

Regional Medicines and Poisons Information Centre NI

Pharmacy Department, Royal Hospital Suite

Grosvenor Road Belfast

Telephone: +44 28 90 63 2032

Fax: +44 28 90 24 80 30

Emergency telephone: 844 892 0111

E-mail address: nirdic.nirdic@belfasttrust.hscni.net

Trade name: **SPRAY BODY 692 EXCLUSIVE PRIMER**

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



health hazard

STOT RE 2 H373 May cause damage to the central nervous system through prolonged or repeated exposure.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02



GHS07



GHS08

Signal word Danger

Hazard-determining components of labelling:

acetone

Low boiling point hydrogen treated naphtha

Solvent naphtha (petroleum), light arom.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics<2%

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the central nervous system through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Trade name: SPRAY BODY 692 EXCLUSIVE PRIMER**Additional information:**

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

Buildup of explosive mixtures possible without sufficient ventilation.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**

Description: Mixture of hazardous substances listed below with nonhazardous additions.

Dangerous components:

CAS: 106-97-8	butane, pure	20-<25%
EINECS: 203-448-7	Flam. Gas 1A, H220	
Index number: 601-004-00-0	Acute Tox. 3, H331	
RTECS: EJ 4200000	Press. Gas (Comp.), H280	
CAS: 67-64-1	acetone	10-<15%
EINECS: 200-662-2	Flam. Liq. 2, H225	
Index number: 606-001-00-8	Eye Irrit. 2, H319; STOT SE 3, H336	
RTECS: AL 3150000		
Reg.nr.: 01-2119471330-49-0001		
CAS: 64742-82-1	Low boiling point hydrogen treated naphtha	≥1-<10%
EINECS: 265-185-4	Flam. Liq. 3, H226	
Index number: 649-330-00-2	STOT RE 1, H372; Asp. Tox. 1, H304	
Reg.nr.: 01-2119458049-33-0002	STOT SE 3, H336	
CAS: 1330-20-7	xylene	5-<10%
Index number: 601-022-00-9	Flam. Liq. 3, H226	
	Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	5-<10%
EINECS: 265-199-0	Flam. Liq. 3, H226	
Index number: 649-356-00-4	Asp. Tox. 1, H304	
Reg.nr.: 01-2119455851-35-0001	Aquatic Chronic 2, H411	
	Acute Tox. 4, H332; STOT SE 3, H335-H336	
EC number: 919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics<2%	≥1-<5%
	Flam. Liq. 3, H226	
	Asp. Tox. 1, H304	
	STOT SE 3, H336	
CAS: 75-28-5	isobutane	1-<5%
EINECS: 200-857-2	Flam. Gas 1A, H220	
Index number: 601-004-00-0	Press. Gas (Comp.), H280	
RTECS: TZ 4300000		
CAS: 13463-67-7	titanium dioxide	1-<5%
EINECS: 236-675-5	Carc. 2, H351	
Index number: 022-006-00-2		
CAS: 74-98-6	propane	1-<5%
EINECS: 200-827-9	Flam. Gas 1A, H220	
Index number: 601-003-00-5	Press. Gas (Comp.), H280	
RTECS: TX 2275000		

Continue on page 4

GB

Trade name: SPRAY BODY 692 EXCLUSIVE PRIMER

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

- **After skin contact:** Generally the product does not irritate the skin.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Remove contact lenses in case of eye contamination and irrigate copiously with clean water for at least 15 minutes trying to hold the eye lids open.

- **After swallowing:** If symptoms persist consult doctor.

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **5.2 Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters

Firefighters should always use protective equipment and breathing apparatus when handling fire coming from these products

5.6 Fire and explosion Hazards**Special protective equipment and fire fighting procedures:**

Mouth respiratory protective device.

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

- **Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Trade name: SPRAY BODY 692 EXCLUSIVE PRIMER**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
 - Do not spray onto a naked flame or any incandescent material.
 - Keep ignition sources away - Do not smoke.
 - Keep respiratory protective device available.
 - Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 - Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**

106-97-8 butane, pure

WEL Short-term value: 1810 mg/m³, 750 ppm
Long-term value: 1450 mg/m³, 600 ppm
Carc (if more than 0.1% of buta-1.3-diene)

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

- **Regulatory information** WEL: EH40/2020
- **Ingredients with biological limit values:**

1330-20-7 xylene

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing
 - Wash hands before breaks and at the end of work.
 - Store protective clothing separately.
 - Avoid contact with the eyes.
 - Avoid contact with the eyes and skin.

Continue on page 6

GB

Trade name: SPRAY BODY 692 EXCLUSIVE PRIMER**Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.

For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)**For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:** Rubber gloves**Eye protection:**

Safety glasses



Tightly sealed goggles

Body protection: Protective work clothing**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information****Appearance:**

Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	-44,5 °C

Flash point: < 0 °C

Flammability (solid, gas): Not applicable.

Autoignition temperature: 296 °C

Trade name: SPRAY BODY 692 EXCLUSIVE PRIMER

- **Decomposition temperature:** Not determined.
- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Risk of explosion by shock, friction, fire or other sources of ignition.
- **Explosion limits:**
 - Lower:** 1.5 Vol %
 - Upper:** 13 Vol %
- **Vapour pressure at 20 °C:** 2,100 hPa
- **Density at 20 °C:** 1.419 g/cm³
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not applicable.
- **Solubility in / Miscibility with water:** Fully miscible.
- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
 - Organic solvents:** 50.8 %
 - VOC (EC)** 829.7-906.7 g/l
 - Solids content (volume):** 35-36.3 %
- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
 - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
 - **Acute toxicity** Based on available data, the classification criteria are not met.
 - **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Dermal LD50 33,198 mg/kg

Inhalative LC50/4 h >89.1 mg/l

106-97-8 butane, pure

Inhalative LC50/4 h 658 mg/l (rat)

Continue on page 8

GB

Trade name: SPRAY BODY 692 EXCLUSIVE PRIMER**471-34-1 calcium carbonate**

Oral LD50 6,450 mg/kg (rat)

67-64-1 acetone

Oral LD50 5,800 mg/kg (rat)

Dermal LD50 20,000 mg/kg (rabbit)

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

Inhalative LC50/4 h 11 mg/l (ATE)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6,800 mg/kg (rat)

Dermal LD50 >3,400 mg/kg (rab)

Inhalative LC50/4 h >10.2 mg/l (rat)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics<2%

Oral LD50 >5,000 mg/kg (rat)

Dermal LD50 >3,000 mg/kg (rab)

13463-67-7 titanium dioxide

Oral LD50 >20,000 mg/kg (rat)

Dermal LD50 >10,000 mg/kg (rabbit)

Inhalative LC50/4 h >6.82 mg/l (rat)

• Primary irritant effect:**• Skin corrosion/irritation** Based on available data, the classification criteria are not met.**• Serious eye damage/irritation**

Causes serious eye irritation.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.**• Additional toxicological information:****• CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)****• Germ cell mutagenicity** Based on available data, the classification criteria are not met.**• Carcinogenicity** Based on available data, the classification criteria are not met.**• Reproductive toxicity** Based on available data, the classification criteria are not met.**• STOT-single exposure**

May cause drowsiness or dizziness.

• STOT-repeated exposure

May cause damage to the central nervous system through prolonged or repeated exposure.

• Aspiration hazard Based on available data, the classification criteria are not met.**SECTION 12: Ecological information****• 12.1 Toxicity****• Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

• 12.2 Persistence and degradability

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

• 12.3 Bioaccumulative potential No further relevant information available.

Trade name: SPRAY BODY 692 EXCLUSIVE PRIMER

- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** UN1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable
- **14.3 Transport hazard class(es)**
- **ADR**



- **Class** 2.5F Gases.
- **Label** 2.1
- **IMDG, IATA**



- **Class** 2.1
- **Label** 2.1
- **14.4 Packing group**
- **ADR, IMDG, IATA** Void

Trade name: **SPRAY BODY 692 EXCLUSIVE PRIMER**

- 14.5 Environmental hazards:
- **Marine pollutant:** No
- 14.6 Special precautions for user Warning: Gases.
- **Hazard identification number (Kemler code):** -
- **EMS Number:** F-D,S-U
- **Stowage Code** SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A.
For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.

- **Segregation Code**

- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.
- **Transport/Additional information:**
- **ADR**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity

- **Transport category** 2
- **Tunnel restriction code** D

- **IMDG**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity

- **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

* SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS02

GHS07

GHS08

- **Signal word** Danger
- **Hazard-determining components of labelling:**

acetone

Low boiling point hydrogen treated naphtha

Solvent naphtha (petroleum), light arom.

Trade name: SPRAY BODY 692 EXCLUSIVE PRIMER

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics<2%

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the central nervous system through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Directive 2012/18/EU**· Named dangerous substances - ANNEX I** None of the ingredients is listed.**· Seveso category** P3a FLAMMABLE AEROSOLS**· Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t**· Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t**· National regulations:****· Additional classification according to Decree on Hazardous Materials, Annex II:**

Carcinogenic hazardous material group III (dangerous).

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.**SECTION 16: Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Contact:

HB BODY S.A

Ms Olympia Stamkou

Ph: +30 2310 790 032

fax: +30 2310 790 033

email: stamkou@hbbody.com

Trade name: SPRAY BODY 692 EXCLUSIVE PRIMER**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment – long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment – long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**

Trade name: SPRAY BODY 692 EXCLUSIVE PRIMER**Annex: Exposure scenario**

- **Short title of the exposure scenario**
- **Sector of Use** SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Process category** PROC7 Industrial spraying
- **Article category** AC7 Metal articles
- **Environmental release category** ERC5 Use at industrial site leading to inclusion into/onto article
- **Technical function** Other
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use** According to directions for use.
- **Duration and frequency** Frequency of use:
- **Physical parameters**
The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.
- **Physical state** Aerosol
- **Concentration of the substance in the mixture** The substance is main component.
- **Used amount per time or activity** Smaller than 100 g per application.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** Use only on hard ground.
- **Other operational conditions affecting worker exposure**
Take precautionary measures against static discharge.
Keep away from sources of ignition - No smoking.
Avoid contact with eyes.
Avoid contact with the skin.
- **Other operational conditions affecting consumer exposure** No special measures required.
- **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures**
Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.
- **Technical protective measures**
Provide explosion-proof electrical equipment.
Use product only in enclosed systems.
Ensure that suitable extractors are available on processing machines
- **Personal protective measures**
The usual precautionary measures are to be adhered to when handling chemicals.
Avoid contact with the eyes.
Pregnant women should strictly avoid inhalation or skin contact.
Tightly sealed goggles
Avoid contact with the skin.
Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Measures for consumer protection**
Ensure adequate labelling.
Observe consumer information and advice on safe use.

Continue on page 14

GB

Trade name: SPRAY BODY 692 EXCLUSIVE PRIMER**· Environmental protection measures****· Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.
Do not allow to reach sewage system.

· Soil

Prevent contamination of soil.
The product is only processed over the concrete collecting basin.

· Disposal measures Ensure that waste is collected and contained.**· Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.**· Waste type** Partially emptied and uncleaned packaging**· Exposure estimation****· Consumer**

This product is to be used by professional technicians only.
Not relevant for this Exposure Scenario.

· Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.