



TECHNICAL DATA SHEET No 701

BODY 650 STONE CHIP

GENERAL TECHNICAL DESCRIPTION

Synthetic rubber-based underbody material with sound deadening / sealing properties and optimum covering ability

Protection from stone chips and rust

Excellent adhesion, quick drying

It can be painted over with all HB BODY Mix Systems

Ready for use

SURFACE

External underneath and internal parts of the car body

PRETREATMENT/CLEANING OF SUBSTRATE



Clean substrate using a soft cloth and 770 ANTISIL NORMAL / 771 ANTISIL FAST DEGREASER.

Make sure the surface is first wiped dry and then air dried.

PRODUCT APPLICATION: Wet-on-wet Fillsealer



Shake well before using:
2 - 3 min



Apply with UBS gun
Pressure: 5 - 6 bar
(73 - 87 psi)
150 - 200 µm (5.9 - 7.9 mil)



5 - 10 min / 23°C (73°F)
Flash off time



Use 340 PLASTOFIX
(Recommended)
Compliant Spray gun
1.3 - 1.5 mm
1x coat = 10 - 15 micron
(0.4 - 0.6mil)



5 - 10 min / 23°C (73°F)
Final flash off time



It can be painted over
with all HB BODY Mix
Systems



Non force dry
2 h / 23°C (73°F)
30 min / 60°C (140°F)
panel temperature

FLASH POINT

9°C / 48°F

SPECIFIC GRAVITY

1.5 g/cm³

SOLID CONTENT

(NO THINNER)

75% Weight

VOC (2004/42/EC)

This product is a special refinish product based on its ingredients and its properties. The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 840 g/L.

2004/42/IIIB(c)(840)840

THEORETICAL COVERAGE

5 - 6 m² / l at 100 micron (4 mil) dry film thickness

CLEANING OF EQUIPMENT

Clean after final use with

767 NITRO THINNER

REMARKS

- It can be also spread by brush to give form and texture

- Allow for additional time for combi spray booths to reach the desired temperature

- Best results when used with HB BODY products

STORAGE SHELF LIFE

- Store in a cool place (+5°C - +25°C) (41°F - 77°F) and use within 12 months for best results.

Guaranteed shelf life of 24 months in unused original containers



Always wear protective equipment



Follow the application instructions mentioned in this TDS

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

AUGUST 2021